

TIMOTEX

LEADERS IN MOBILE WEIGHING



SUPAWEIGH

WEIGHING SCALES



Lift, weigh and go!

TIMOTEX

LEADERS IN MOBILE WEIGHING

The Supaweigh XL and Loadchecker weighing scales are approved and supplied for all leading makes of forklift truck. The Supaweigh can be fitted to counterbalance, reach, powered pedestrian, narrow aisle, side loaders and container handlers as well as loading shovels, wheeled loaders, skid steers, excavators, tractor loaders and R.T. Handlers



XL model shown

FEATURES:

- Unmatched accuracy
- Comprehensive screen prompts for easy operation
- Tactile keypad
- Lift truck overload alarm
- Accuracy unaffected by a change of lifting attachment
- Styled, diecast case sealed to IP65
- Reliable and maintenance free
- Calibration certificate traceable to national standards
- CE marked
- Solid state memory for data storage up to 10 years

XL FEATURES:

- 0-9 keypad for fast entry of digital tare and 10-digit product/identification code which appears on printout
- 4 memory channels to store load data
- Target load entry linked to target alert



Turns your lift truck into a mobile weighing station

SUPAWEIGH

WEIGHING SCALES



Loadchecker model shown

GUARANTEED UNRIVALLED ACCURACY, RELIABLE & COST EFFICIENT

- Typically +/- 10kg on a lift truck to 5000kg lifting capacity. That is unquestionably better than any other scale of its type on the market today
- Saves time-consuming trips to and from fixed scales
- Saves time through stocktaking by weight
- Checkweighs incoming supplies and outgoing products
- Can help to avoid overloading of forklifts/vehicles/racking
- Helps to reduce truck wear and tear
- Does not affect driver visibility or truck lifting capacity
- Promotes safer use of lift truck



Lift truck weighing has never been easier

SPECIFICATION

Power supply:	Voltage 12 volts DC nominal	
Current:	with printer 430mA; nominal 5A peak without printer 380mA maximum	
Filtering:	Protected against interference, supply excursions and transient voltages (60dB attenuation at 10Mhz)	
Display case:	Heavy gauge steel bracket mounting with locking device	
Keypad:	Touch sensitive. Resistant to ethanol, glycol, isoproporal, acetaldehyde, aliphatic hydrocarbons, xylene, perchloroethylene, 1.1.1. trichloroethane, ethyl acetate, diethylether, acetone, methylethyl ketone	
Performance:	Up to 200 tonnes	
Accuracy:		Typical Resolution
Forklift Truck	1000-5000kg	10kg maximum
	5000-10,000kg	10 or 20 kg
	10,000 or more	10 or 20 or 50kg
Circuitry:	Solid state microprocessor controlled	
Display:	120mm x 25mm transfective liquid crystal. Large 9mm high charcaters	
Display lighting:	Automatic LED backlighting	
Printers:	Thermal and Dot matrix	
Printer Memory:	Up to 400 loads divided across four memory channels	
Printout:	Time (24 hr clock), date, totaliser channel, load weight, load count, 10 digit product code, load weight. Customised options available	
Weighing Modes:		
XL:	Subtractive from target load linked to load alert	
Loadchecker:	Additive to one memory channel	
Keyboard*:	Alpha numeric, standard QWERTY36 key pad, sealed to IP67	
RS232*:	Bi-directional to transmit printer memories at 1200 baud, 8 bit, no parity, 1 stop bit	
Dimensions		
XL/Loadchecker	w 200mm x d 85mm x h 125mm	
Dot Matrix Printer	w 128mm x d 122mm x h 90mm	
Thermal Printer	w 135mm x d 130mm x h 64mm	
Operating Temp		
With Printer	0°C to 60°C	
Without Printer	-10°C to 60°C	
Storage Temp		
Without Printer	-20°C to 60°C	

CE Marked

*Only available for Supaweigh XL scale

Timotex has a policy of continuous product improvement and reserves the right to change specifications without prior notice

OPTIONS

- Choice of Thermal or Tally Roll printers
- Alpha numeric keyboard for detailed product code entry
- RS232 bi-directional interface to link to a PC
- Radio data transfer
- Customised software to suit individual requirements
- Multi-lingual screen prompts in most European languages



TIMOTEX

LEADERS IN MOBILE WEIGHING

Timotex Limited

Lodge Road, Stourport on Severn, Worcestershire, DY13 9HE, UK

Tel: +44 (0) 1299 823850

Fax: +44 (0) 1299 825110

Email: sales@timotex.co.uk

Web: www.timotex.co.uk



Lift, weigh and go!